

SPR 120

SIMAG

120 kg Self-contained Ice Machine

Complete range: SPR 80 - SPR 120 - SPR 200

Technical features

- Electronic control
- Stainless steel bodywork - scotch brite
- Air or water cooled
- Direct transmission
- Easily accessible components
- Low power and water consumption
- Reduced dimensions
- Continuous production



Internal bin capacity




55 kg of ice

Type of ice

Flake ice



Residual water content 25 %



Voltage

230/50/1 Standard version

220-240/60/1 Available on demand

Machine dimensions

Net size WxDxH 920 x 594 x 867 mm

Net weight 69 kg

Shipping size WxDxH 980 x 650 x 960 mm

Shipping weight 78 kg

Technology and Certifications



MILANO OFFICE
Sales Dept.
Tel. +39 02 93900215
e-mail: sales@simag.it
Service Dept.
Tel. +39 02 93960357
e-mail: service@simag.it

SIMAG FAR EAST
Singapore Office
Tel. ++65 6738 5393
e-mail: scotsman@scotsman.com.sg

www.simag.it

SIMAG

Complete range: SPR 80 - SPR 120 - SPR 200



	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar	5 bar
Electrical voltage	-10 %	+10 %

Model	Voltage	Daily production kg	Power input Watt (*)	Refrigerant		Fuse A	Consumptions (**)		
		10°C/10°C		Type	Charge kg		kWh/100kg	kWh/24h	Water l/h
SPR 120 A	230/50/1	120	500	R134a	0.440	10	n.a.	n.a.	4.2
SPR 120 W	230/50/1	120	500	R134a	0.380	10	n.a.	n.a.	29.0
SPR 120 A	220/60/1	120	n.a.	R134a	n.a.	10	n.a.	n.a.	4.6
SPR 120 W	220/60/1	120	n.a.	R134a	n.a.	10	n.a.	n.a.	29.0

(*) Power Input: at 43°C Ambient Temperature

(**) Water Consumption: at 32°C Air and 21°C Water